

MODELLO - MODEL - MODELE - MODELL - MODELOS	ETS 15	
Produzione (C/H) - Production (D/H) - Production (A/H) - Produktion (T/S) - Produccion (P/H)	n°	75
Motore avanzamento - Feed motor - Moteur avancement - Leistg. Vorschubmotor - Motor de tração	kW	0,18
Tensione - Std input voltage - Tension - Stromspannung - Tension	V	400/3/50 Hz
Alimentaz. acqua - Feed water - Eau d'alimentation - Wasserzulauf - Calentamiento agua	°C	55
Pres. aliment. acqua - Water feed. pressure - Pression aliment. eau - Wasserdruck	bar	1,5 ÷ 6
Dotazione cestelli - Std supplied baskets - Dotation paniers - Ausstattung Körbe - Dotacion cesta	n°	4
Passaggio utile cesto - Basket useful passage - Passage utile panier - Durchschubhoehe - Altura util	mm	500x430

LAVAGGIO - WASH - LAVAGE - SPÜLUNG - LAVADO		
Cap. vasca - Tank capacity - Capacité cuve - Tankfüllung - Capacidad cuba	l	87
Potenza pompa - Pump power - Puissance pompe - Pumpenleistung - Potencia bomba	kW	1,3
Riscaldamento vasca - Tank heating - Rechauffement cuve - Tankheizung - Calentamiento cuba	kW	9
Temperatura - Temperature - Température - Temperatur - Temperatura	°C	55

RISCIACQUO - RINSE - RINÇAGE - NACHSPÜLUNG - ACLARADO		
Capacità boiler - Capacity - Capacité - Leistung - Capacidad	l	24
Temperatura - Temperature - Température - Temperatur - Temperatura	°C	85
Riscaldamento boiler - Boiler heating - Surchauffeur - Boilerheizung - Calentamiento boiler	kW	18
Consumo acqua - Water consumption - Consommation eau - Wasserverbrauch - Consumo agua	l	300
(*) Pot. massima assorbita - Max absorbed power - Puissance max absorbée Max Leistungsaufnahme - Maxima potencia absorbida	kW	19,3

IMPIANTI SUPPL. - SPECIAL EQUIPMENTS - EQUIPEMENTS SUPPLEMENTAIRES - OPTIONAL					
	Modello	Dimensioni mm	Motore - Motor Moteur - Motor	Riscaldamento - Heating Chauffage - Heizung	(*) Resistenze vasca e boiler "in scambio". Tank and boiler heating element "in exchange". Résistance cuve et surchauffeur fonction- nant en échange. Boiler- und Waschbecken- heizung im Wechsel eingeschaltet. Resistencias de cuba y caldera con intercambio.
Imp. asciugatura Drying unit Equipement de séchage Trockenanlage Tunnel secadura	IA60	600x840x2230	kW 0,75 m³/h 1300	kW 8,4	
Cappa aspirazione Extraction Hood Extracteur buées Dampfanzugshaube Aspirador vapores	CA				
	CAM		kW 0,2		